

## STUMP CUTTERS FOR EXCAVATORS

# SCL/EX/VT

Disc stump cutters for excavators.



28-45 gal/min



7-15 t



### STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor (28-45 gpm)	Poly Chain Belt Transmission
Flow control system valve	Bulkhead for hydraulic connections
Safety and anticavitation valve	Hydraulic front hood
Enclosed / anti dust machine body	Screwed protection chains
Motor enclosed in the frame	Supporting service leg

### OPTIONS

80/50cc variable torque hydraulic piston motor (20-32 gpm)	Rear fixed heel
Customized setting hydraulic motor	Customized attachment bracket with pins
Diverter valve (plug in and play)	Customized attachment bracket with pins and leg
Not supplied with hoses	Case drain required

### MODEL

### SCL/EX/VT

<b>Flow rate</b> (gal/min)	28-45
<b>Pressure</b> (PSI)	2600-5080
<b>Excavator weight</b> (t)	7-15
<b>Total width</b> (in)	30
<b>Weight</b> (lbs)	1664
<b>Rotor diameter</b> (in)	26
<b>No. teeth</b> type L1+L2+L3+L4	12+3+12+3

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



**L1**  
(standard)



**L3**  
(standard)



**L4**  
(standard)



**L2**  
(standard)