

TILLERS FOR SPECIAL BUILT CARRIERS

500S



from 450 to 650 HP



Ø 24 in max



D 20 in

FORESTRY TILLER FOR HYDRAULIC CARRIERS.

The transmission on the 500S was developed for use with 450 HP to 650 HP dedicated carriers. The 500S is designed for mulching stumps up to a diameter of 24" and roots up to 20" in depth. Our research, technology and heavy duty construction enable this machine to be reliable and have a long working life.



STANDARD EQUIPMENT AND OPTIONS


Considering the various available options and high level of customization, the final configuration will be specified upon request



Variable manual displacement hydraulic motor



Hydraulically controlled hood to adjust final product



Dual transmission with side gearbox
reduces the speed of the rotor thereby reducing tool wear

MODEL	Engine (HP)		Flow rate (gal/min)		Pressure (PSI)		Working width (in)	Total width (in)	Weight (lbs)	Max working depth (in)	Max shredding diameter (in)	No. teeth type B/3 + STC/3/FP + STC/FP
	min	max	min	max	min	max						
500/S - 225	450	650	150	205	5000		91	116	12670	20	24	104+4+4
500/S - 250	450	650	150	205	5000		101	126	13120	20	24	128+4+4
500/S - 275	450	650	150	205	5000		110	135	13670	20	24	152+4+4

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.