

## FORESTRY MULCHERS

# UML/S/DT

Forestry mulcher for PTO tractors with fixed tooth rotor.



130-190 hp



Ø 10 in max



### STANDARD EQUIPMENT

Hydraulic rear hood	Transmission with belts
Inner anti wear clad plates FCP	Gearbox with freewheel
Enclosed machine body	PTO shaft with cam clutch
Centralized greasing hub	Bolted-on rotor shafts (in forged steel)
Hydraulic hoses integrated in the frame	Interchangeable bolted on spike counter-blade
Cylinder protection	Adjustable skids
Bolted on protection chains	Supporting service leg

### OPTIONS

Frontal attachment (UML/S/DT 225)	W style self aligning device between PTO drive shaft/gearbox
Bolt-on chain's protection plates	Special skids to go underground
Multiple tooth options	Mechanical guard frame
Hydraulic top link	Hydraulic guard frame
Z style self ranging system of the PTO drive shaft/gearbox	Extra ripper for guard frame
IVT - CVT or creeper transmission strongly recommended	Forestry tires and carrier belly pan strongly recommended

MODEL	UML/S/DT 200	UML/S/DT 225
<b>Engine</b> (hp)	130-190	130-190
<b>PTO</b> (rpm)	1000	1000
<b>Working width</b> (in)	81	91
<b>Total width</b> (in)	96	105
<b>Weight</b> (lbs)	3726	4023
<b>Rotor diameter</b> (in)	17.8	17.8
<b>Max shredding diameter</b> (in)	10	10
<b>No. teeth</b> type C/3+C/3/SS	42+2	48+4
type I+C/3/SS	60+2	66+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

### ROTOR TYPE C



**C/3**  
(standard)



**C/3/HD**  
(option)



**BL Blade**  
(option)



**K/3**  
(option)

### ROTOR TYPE I



**I**  
(option)



**C/3/SS**  
(side scraper)