

FORESTRY MULCHERS FOR EXCAVATORS

DML/HY - DML/HY/VT

Forestry mulcher with fixed tooth rotor for excavators.



17-36 gal/min



Ø 5 in max



5-13 t

STANDARD EQUIPMENT

17/34cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (17-33 gpm) (DML/HY)	Bulkhead for hydraulic connections
55/38cc variable torque hydraulic piston motor (21-36 gpm) (DML/HY/VT)	Front hood with mechanical adjustment
Flow control system valve	Rear hood with mechanical adjustment
Safety and anticavitation valve	Protection chains
Enclosed / anti dust machine body	Supporting service leg
Motor enclosed in the frame	Welded counterblades
Belt transmission	

OPTIONS

32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (28-53 gpm) (DML/HY)	Hydraulic front hood
Customized setting hydraulic motor	Customized attachment bracket with pins
Diverter valve	Customized attachment bracket with pins and leg
Hydraulic rear hood	Multiple tooth options
Not supplied with hoses	Case drain required

MODEL	DML/HY 75	DML/HY 100	DML/HY 125	DML/HY/VT 75*	DML/HY/VT 100*	DML/HY/VT 125*
Flow rate (gal/min)	13-53	13-53	13-53	13-53	13-53	13-53
Pressure (PSI)	2600-3600	2600-3600	2600-3600	2600-5080	2600-5080	2600-5080
Excavator weight (t)	5-13	5-13	5-13	5-13	5-13	5-13
Working width (in)	31	39	49	31	39	49
Weight (lbs)	915	981	1135	926	992	1146
Rotor diameter (in)	11.8	11.8	11.8	11.8	11.8	11.8
Max shredding diameter (in)	5	5	5	5	5	5
No. blades type E	20	24	30	20	24	30

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

*Variable displacement hydraulic motor.



Blade E
(standard)

Blade E/HD
(option)