

FORESTRY MULCHERS FOR SKID STEERS

PMM/SSL

Brush mulcher with hammer/flail rotor for skid steers.

A universal mulcher suitable for mulching saplings bushes, crop residues and grass. Thanks to its “floating system”, the mulcher’s rotor adheres perfectly to the terrain, ensuring a homogeneous material after mulching. The support roller, larger in comparison to

other attachments, guarantees the best performance even on particularly damp terrain. The machine can be equipped with hammers for mulching material up to 3 in diameter or grass flail to better respond to the various needs of the customer.



65-100 hp



Ø 3 in max



Steel counter-blades
helps mulch material into a smaller final size



Self leveling protection flaps



Attachment plate with self leveling device
adapts to all types of terrain



Self cleaning rear roller with integrated skids



MAIN OPTIONS



Multiple flail

STANDARD EQUIPMENT

32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve	Self levelling protection flaps
Motor enclosed in the frame	Supporting service leg
Belt transmission	Welded counterblades
Hydraulic hoses	Self cleaning rear roller with integrated skids
Front hood with mechanical adjustment	Attachment plate with self levelling device
Adjustable skids	

OPTIONS

Customized setting hydraulic motor	Stronger bearing for back roller
Possibility to have the rotor equipped with PML hammers or Y-flail	
Case drain required	

MODEL	PMM/SSL-175	PMM/SSL-200
Engine (hp)	65-100	70-100
Flow rate (gal/min)	15-33	15-33
Pressure (PSI)	2600-3600	2600-3600
Working width (in)	70	80
Total width (in)	79	86
Weight (lbs)	1874	2006
Rotor diameter (in)	17.3	17.3
Max shredding diameter (in)	3	3
No. hammers type PMM	22	24
No. flails type Y/3	22	24

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



HAMMER PMM
(standard)



FLAIL Y/3
(option)