

FORESTRY MULCHERS FOR EXCAVATORS

BL3/EX/VT

Forestry mulcher with bite limiter technology.



32-55 gal/min



Ø 8 in max



14-20 t

STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor (32-55 gpm)	Poly Chain Belt Transmission
Flow control system valve	Bulkhead for hydraulic connections
Diverter valve	Hydraulic rear hood
Safety and anticavitation valve	Adjustable skirts
Enclosed / anti dust machine body	Rotor Bite Limiter
Motor enclosed in the frame	

OPTIONS

Customized setting hydraulic motor	Hydraulic thumb
Hydraulic front hood for excavator AUX line	Spike Pro counter-blade
Rear deflector	Customized attachment bracket with pins
Front fixed thumb bracked	Sonic System
Not supplied with hoses	Case drain required

MODEL	BL3/EX/VT 125	BL3/EX/VT 150
Flow rate (gal/min)	32-55	32-55
Pressure (PSI)	2600-5080	2600-5080
Excavator weight (t)	14-20	14-20
Working width (in)	53	62
Weight (lbs)	2138	2381
Rotor diameter (in)	16.5	16.5
Max shredding diameter (in)	8	8
No. blades type BL + C/3/SS	20+2	24+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



BL Blade
(standard)



C/3/SS
(side scraper)