

NEW SONIC SYSTEM

FORESTRY MULCHERS FOR EXCAVATORS

UML/S/EX/VT

Forestry mulcher with fixed tooth rotor for excavators.



38-63 gal/min



∅ 12 in max



18-25 t

STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor (38-63 gpm)	Bulkhead for hydraulic connections
Flow control system valve	Hydraulic front hood
Safety and anticavitation valve	Inner anti wear clad plates FCP
Enclosed / anti dust machine body	Screwed protection chains
Motor enclosed in the frame	Interchangeable counterblades
Poly Chain Belt Transmission	

OPTIONS

160/108cc variable torque hydraulic piston motor (62-79 gpm)	Customized attachment bracket with pins and leg
Customized setting hydraulic motor	Multiple tooth options
Diverter valve (plug in and play)	Rotor Bite Limiter
Additional reinforced side plates	Sonic System
Customized attachment bracket with pins	
Not supplied with hoses	Case drain required

MODEL	UML/S/EX/VT 125	UML/S/EX/VT 150
Flow rate (gal/min)	38-63	38-63
Pressure (PSI)	3200-5080	3200-5080
Excavator weight (t)	18-25	18-25
Working width (in)	53	62
Weight (lbs)	3197	3417
Rotor diameter (in)	17.7	17.7
Max shredding diameter (in)	12	12
No. teeth type C/3+C/3/SS	26+4	32+4
type I+C/3/SS	36+2	42+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE C



C/3
(standard)



C/3/HD
(option)



BL Blade
(option)



K/3
(option)

ROTOR TYPE I



I
(option)



C/3/SS
(side scraper)