

NEW SONIC SYSTEM

FORESTRY MULCHERS FOR SKID STEERS

UML/SSL - UML/SSL/VT

Forestry mulcher with fixed tooth rotor for excavators.



75-120 hp



Ø 8 in max

STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor (32-53 gpm) (UML/SSL/VT)	Hydraulic hoses
Hydraulic piston motor 63cc with relief and anticavitation valve (38-42 gpm) (UML/SSL)	Hydraulic front hood
Safety and anticavitation valve	Adjustable skids
Enclosed / anti dust machine body	Working pressure control gauge
Motor enclosed in the frame	Guard frame
Belt transmission (UML/SSL)	Dual row protection chains
Poly Chain Belt Transmission (UML/SSL/VT)	Welded counterblades

OPTIONS

Customized setting hydraulic motor (UML/SSL/VT)	Multiple tooth options
Diverter valve (plug in and play)	Rotor Bite Limiter (UML/SSL/VT)
Oil cooler kit	Sonic System (UML/SSL/VT)
Case drain required	

MODEL	UML/SSL 125*	UML/SSL 150*	UML/SSL 175*	UML/SSL/VT 125*	UML/SSL/VT 150*	UML/SSL/VT 175*
Power (hp)	75-120	75-120	75-120	75-120	75-120	75-120
Flow rate (gal/min)	38-42	38-42	38-42	32-53	32-53	32-53
Pressure (PSI)	2901-5076-	2901-5076-	2901-5076-	2900-5000	2900-5000	2900-5000
Working width (in)	53	62	72	53	62	72
Total width (in)	65	74	83	65	74	83
Weight (lbs)	2646	2866	3086	2646	2866	3086
Rotor diameter (in)	16.5	16.5	16.5	16.5	16.5	16.5
Max shredding diameter (in)	8	8	8	8	8	8
No. teeth type C/3+C/3/SS	26+2	32+2	36+2	26+2	32+2	36+2
type I+C/3/SS	36+2	42+2	50+2	36+2	42+2	50+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

*Variable displacement hydraulic motor.

ROTOR TYPE C



C/3
(standard)



C/3/HD
(option)



BL Blade
(option)



K/3
(option)

ROTOR TYPE I



I
(option)



C/3/SS
(side scraper)