

## FORESTRY TILLERS

# SSL SPEED

Forestry tiller for PTO tractors with fixed teeth rotor.



100-220 hp



Ø 12 in max



Depth 12 in

### STANDARD EQUIPMENT

Hydraulic rear hood	Friction clutches (SSL/DT SPEED)
Enclosed machine body	PTO shaft with cam clutch
Inside lateral protection	Bolted-on rotor shafts (in forged steel)
Protection chains	Welded steel counter-blades
Transmission with side gearbox	Adjustable counter-blade (forest)
Gearbox with freewheel	

### OPTIONS

Multiple tooth options	Hydraulic guard frame
Hydraulic top link	Hydraulic support roller
IVT - CVT or creeper transmission strongly recommended	Forestry tires and carrier belly pan strongly recommended

MODEL	SSL SPEED 150	SSL SPEED 175	SSL/DT SPEED 200	SSL/DT SPEED 225	SSL/DT SPEED 250
<b>Engine</b> (hp)	100-160	110-160	120-220	130-220	140-220
<b>PTO</b> (rpm)	1000	1000	1000	1000	1000
<b>Working width</b> (in)	63	72	82	91	101
<b>Total width</b> (in)	76	85	94	104	113
<b>Weight</b> (lbs)	4409	4762	5732	6195	6680
<b>Rotor diameter</b> (in)	23.4	23.4	23.4	23.4	23.4
<b>Max shredding diameter</b> (in)	12	12	12	12	12
<b>Max working depth</b> (in)	12	12	12	12	12
<b>No. teeth</b> type B/3+C/3/SS	44+4	50+4	58+4	66+4	74+4

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

### ROTOR TYPE B



**B/3**  
(standard)



**B/3/HD**  
(option)



**G/3**  
(option)



**G/3/HD**  
(option)



**C/3/SS**  
(side scraper)