
MULTITASKS


SFM

Stone crusher, forestry tiller and mulcher for PTO tractors with fixed tooth rotor.

The SFM is the answer to a very demanding market and tough applications. This unit combines the functionality and efficiency of a forestry mulcher, forestry tiller and rock crusher. The SFM is equipped with interchangeable bolt-on counter blades, FCP inserts (FAE clade plate) and grill making this machine unique in its category. These options along with FAE's new smoother, more aggressive design differentiate FAE from the rest.



helps keep the correct operating angle between the PTO shaft and the power take-off



Hydraulically controlled rear door adjust final product size while machine is working



Forged and hardened interchangeable counter-blades for longest working life





Adjustable extended 3 point linkage fits perfectly with any kind of tractor

Transmission with side gearbox maximize the power delivered to the rotor



System protection chains the chains are fixed on plate and these plates screwed to the frame



MAIN OPTIONS



W style self aligning device between PTO drive shaft/gearbox allows the machine to work

at several angles without damaging the PTO



Bolted grid on rear door allows more adjustment of the final material size



Hydraulically adjustable skids allow you to control the rotor depth and prevent material from exiting out the sides



Hydraulic support roller (D. 14 in - D. 20 in) helps with compaction and working uneven terrain



160-300 hp



Ø 8 in max (stones) Ø 14 in max (trees) Ø 18 in max (stump)



Depth 12 in



STANDARD EQUIPMENT

Hydraulic rear hood	Side gearbox with oil cooling system	
Inner anti wear clad plates FCP	Gearbox with freewheel	
Interchangeable inner antiwear plates in Hardox®	Friction clutches	
Adjustable extended 3 point linkage	PTO shaft with cam clutch	
Enclosed machine body	Bolted-on rotor shafts (in forged steel)	
Hydraulic hoses integrated in the frame	Hydraulic top link	
Cylinder protection	Z style self ranging system of the PTO drive shaft/gearbox	
Inside lateral protection	Forged and hardened interchangeable counter-blades	
Bolted on protection chains	Adjustable Hardox® counter-blade	
Transmission with side gearbox		

OPTIONS

Bolted grid on rear hood	Hydraulically adjustable skids
Bolt-on chain's protection plates	Hydraulic guard frame
High Speed Transmission	Dozing blades
W style self aligning device between PTO drive shaft/gearbox	Hydraulic support roller
IVT - CVT or creeper transmission mandatory	Forestry tires and carrier belly pan strongly recommended

MODEL	SFM-200	SFM-225	SFM-250
Engine (hp)	160-300	170-300	180-300
PTO (rpm)	1000	1000	1000
Working width (in)	81	91	100
Total width (in)	94	104	113
Weight (lbs)	8333	9000	9667
Rotor diameter (in)	26.4	26.4	26.4
Max shredding diameter stones (in)	8	8	8
trees (in)	14	14	14
stump (in)	18	18	18
Max working depth (in)	12	12	12
No. teeth type F/3+STC/3/FP	50+6	58+6	62+6

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.



TOOTH F/3

