

NEW


FORESTRY MULCHERS FOR EXCAVATORS

RQL/HY

Forestry mulcher for powerpack vehicles and wheeled excavators from 10 to 15 t.

The RQL/HY is a lightweight and versatile forestry mulcher for powerpack vehicles and wheeled excavators from 10 to 15 t. It is designed to cut grass, shrubs and trees up to 6 inches in diameter. The RQL/HY is ideal for carrying out maintenance of road and railway embankments. The sturdy fixed-tooth rotor is balanced to ensure no vibration. The Direct Drive motor of the RQL/HY is positioned on the left to keep the center of gravity closer to the carrier.

It reduces maintenance to a minimum and allows more compact body dimensions for increased maneuverability. In the inner chamber, interchangeable bolt-on spike counter blades ensure fine shredding of all types of vegetation. The head can be fitted with C/3/MINI teeth or BL/MINI blades. It is available in three widths: RQL/HY-125, RQL/HY-150 and RQL/HY-175.



MAIN OPTIONS



Mechanical push frame



Customized attachment bracket

- 24-53 gal/min
- Ø 6 in max
- 10-15 t



STANDARD EQUIPMENT

32 cc hydraulic piston motor	12 V Diverter valve
Hydraulic motor with flushing valve	Fittings for hydraulic connections
Direct-drive transmission	Interchangeable bolt-on Spike PRO counter blades
Motor enclosed in the frame	Adjustable skids
Enclosed, dust-resistant machine body	Interchangeable protection chains
Flow control system valve with integrated safety and anticavitation valves	Interchangeable forged steel rotor shafts
Hydraulically adjustable rear hood	Rotor with teeth C/3/MINI

OPTIONS

63 cc hydraulic piston motor	Customized attachment bracket with pins
24 V Diverter valve	Customized attachment bracket with pins and leg
Control box for Diverter valve	Tooth options
Mechanically adjustable push frame	Attachment plate with self-leveling device
Support roller	
Not supplied with hoses	Case drain required

MODEL	RQL/HY-125	RQL/HY-150	RQL/HY-175
Flow rate (gal/min)	24-53	24-53	24-53
Pressure (PSI)	2600-5080	2600-5080	2600-5080
Excavator weight (t)	10-15	10-15	10-15
Working width (in)	49	58	68
Total width (in)	66	75	84
Weight (lbs)	1235	1345	1477
Rotor diameter (in)	14.2	14.2	14.2
Max shredding diameter (in)	6	6	6
No. teeth type C/3/MINI	26	32	36

Options may have reflects on weights and dimensions.



STUMP CUTTERS FOR EXCAVATORS

Our professional, hydraulic driven excavator stump cutters can be utilized for easy and quick removal of stumps.



SCL/HY

Disc stump cutters for excavators.



SCL/EX

Disc stump cutters for excavators.



SCM/EX

Disc stump cutters for excavators.



IT REACHES AND OVERCOMES OBSTACLES.

MODEL	1 - 10 t	10 - 25 t
SCL/HY	4 - 7,5 t	
SCL/EX	7 - 15 t	
SCM/EX		14 - 24 t