FORESTRY MULCHERS FOR EXCAVATORS

BLO/EX

Forestry mulcher with Bite Limiter technology for excavators up to 5 tons.

The BLO/EX forestry mulcher for 2-5 ton excavators can shred material up to 3 inches in diameter. Bite Limiter technology is ideal for high productivity vegetation management, designed with reliable and efficient shredding and easy maintenance in mind.

The BLO/EX's Direct Drive motor minimizes maintenance and makes it possible to have an extremely compact machine body. The BLO/EX can be equipped with BL/MINI blades and C/3/MINI teeth.



Hydraulic block with flow control valve in the motor

Fixed thumb bracket built into the frame useful for moving materials that need to be mulched



Direct Drive Motor

for less maintenance and reduced size

Rotor Bite Limiter

special steel profiles limit the blades' reach and optimize productivity

Adjustable rear deflector

controls mulched material output for greater safety

MAIN OPTIONS



Customized attachment bracket kit with customized pins



Attachment plate with self-leveling device (optional) adapts to all types of terrain



8-24 gal/min



Ø 3 in max



2-5 t

STANDARD EQUIPMENT

STATESARE EQUITATE TO		
11 cc-gear hydraulic motor (BL0/EX-50)	25 cc-gear hydraulic motor (BL0/EX-100)	
16 cc-gear hydraulic motor (BLO/EX-75)	Thumb bracket	
Flow Control system valve with integrated safety and anticavitation valves	Direct-drive transmission	
Enclosed, dust-resistant machine body	Interchangeable forged steel rotor shafts	
Motor enclosed in the frame	Bite Limiter Rotor	
Hydraulic hoses	Wear-resistant interchangeable Hardox® soles	
Deflector		

OPTIONS

Customized attachment bracket kit with customized pins	11 cc-gear hydraulic motor (BL0/EX-75)
Custoffized attachment bracket kit with custoffized pins	Tree-gear riyaradiic motor (BEO/EX-75)
Attachment plate with self-leveling device	Multiple tooth options
16 cc-gear hydraulic motor (BLO/EX-50 and BLO/EX-100)	

MODEL	BL0/EX-50	BL0/EX-75	BL0/EX-100
Flow rate (gal/min)	8-18	8-18	18-24
Pressure (PSI)	2600-3600	2600-3600	2600-3600
Excavator weight (t)	2-4	3-4	4-5
Working width (in)	22	31	39
Total width (in)	40	49	58
Weight (lbs)	470	553	728
Rotor diameter (in)	12	12	12
Max shredding diameter (in)	3	3	3
No. blades type BL/MINI	10	14	20
No. tooth type C/3/MINI	10	14	20

The technical data in this catalogue may be altered without prior notice.







TOOTH C/3/MII